

Vipe P Datasheet



Performance



Lumen Output	Wattage	lm/cW
574 lm	8.1 W	70.9 lm/cW
716 lm	10.2 W	70.2 lm/cW
861 lm	12.2 W	70.6 lm/cW
1,079 lm	15.3 W	70.5 lm/cW

Rated Supply Voltage	220 – 240 V
AC Voltage Range	198 – 264 V
Mains Frequency	50/60 Hz
Output LF current ripple @ 120Hz (Flicker)	<5%
Overvoltage Protection	320 V
In-rush Current	14 A
THD	<10%
Dimming Range	15 – 100%
Operating Temperature	-25. ±60 °C
Colour Rendering	Ra>82
Cutout	Ø75mm
Dimensions	Ø90 x 115mm
Weight	1.2kg
Warranty	5 Years
Certification	CE, ROHS

Emergency

Standard Lumen Output	BLF	Emergency Lumen Output
574 lm	32%	184 lm
716 lm	25%	179 lm
861 lm	18%	155 lm
1,079 lm	17%	183 lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0 – 60°C
Power Efficiency	95%
Certification	CE, ROHS



BumbleBee

Tel: 01489 878 406 Email: info@bumblebee-lighting.co.uk Web: bumblebee-lighting.co.uk
 BumbleBee, Unit 11, Lycroft Business Park, Park Lane, Upper Swanmore, Southampton, SO32 2QQ

Vipe P Datasheet



Order Codes

Vipe P		VIP.P
Lumen Output	570lm	-570
	720lm	-720
	860lm	-860
	1080lm	-1080
Colour Temperature	3000K	-3K
	4000K	-4K
	5000K	-5K
Beam Angle	15° Beam	-15
	24° Beam	-24
	30° Beam	-30
	36° Beam	-36

Extras

Type	Options	Code
Body	Adjustable Tilt	+ADJ
Dimming	1-10V Dimming	+110V
	DALI Dimming	+DALI
Emergency	3 Hour Facility	+EM
	3 Hour Self Test	+EMST
	3 Hour Central Test	+EMCT

BumbleBee