

Brevis D



Performance

Lumen Output	Wattage	lm/cW
1360lm (4000K)	15.2W	89.5 lm/cW
1796lm (4000K)	20.4W	88.0 lm/cW

Rated Supply Voltage	220 – 240 V
AC Voltage Range	198 – 264 V
Mains Frequency	50/60 Hz
Output LF current ripple @ 120Hz (Flicker)	<5%
Overvoltage Protection	320 V
In-rush Current	2.5 A
THD	<10%
Dimming Range	15 – 100%
Operating Temperature	-25. +60 °C
Colour Rendering	Ra>82
IP Rating	IP44
Surface Fixing	95mm
Suspended Fixing	95mm (2m suspension)
Dimensions	Ø195 x 130mm
Weight	2.8 kg
Warranty	5 Years
Certification	CE, ROHS

Emergency (optional)

Standard Lumen Output	BLF	Emergency Lumen Output
1360lm	17%	231 lm
1796lm	13%	233 lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0 – 60°C
Power Efficiency	95%
Certification	CE, ROHS

90°

