

Hornet 300x1500mm Datasheet



Performance

Typical Lumen Outputs	Wattage	lm/cW
3703 lm	31.8 W	116.4 lm/cW
4105 lm	35.1 W	117.0 lm/cW



Rated Supply Voltage	220 – 240 V
AC Voltage Range	202 – 250 V
Mains Frequency	50/60 Hz
Output LF current ripple @ 120Hz (Flicker)	<4%
Overvoltage Protection	320 V
THD	<20%
Dimming Type	DALI
Dimming Range	1 – 100%
Operating Temperature	-25 +60 °C
Longevity	50,000 hours
UGR Rating	<19
Colour Rendering	Ra>82
Dimensions	295 x 1495 x 85mm
Weight	6.5 kg
Warranty	5 Years
Certification	CE, ROHS

Emergency

Lumen Output	BLF	Emergency Lumen Output
3703 lm	15%	555 lm
4105 lm	13%	534 lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 2.4V 2.5Ah
Parasitic Load	1.2W
Operating Temperature	0 – 60°C
Power Efficiency	95%
Certification	CE, ROHS

120°



BumbleBee

Tel: 01489 878 406 Email: info@bumblebee-lighting.co.uk Web: bumblebee-lighting.co.uk
 BumbleBee, Unit 11, Lycroft Business Park, Park Lane, Upper Swanmore, Southampton, SO32 2QQ