

Hornet 300x1500



Performance

Lumen Output	Wattage	lm/cW
3702lm (4000K)	25.6 W	144.6
4104lm (4000K)	28.6 W	143.5

Diffuser	Frosted Microprism (optional)
Rated Supply Voltage	220–240 V
AC Voltage Range	202–250 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<1%
Overvoltage Protection	320 V
In-rush Current	12 A
THD	<20%
Dimming Type (optional)	DALI
Operating Temperature	-25 +60 °C
UGR Rating	<19
Colour Rendering (3 SDCM)	Ra>82
Longevity (L70/B10)	70,000 hours
IP Rating	IP44
Dimensions	299 x 1499 x 80 mm
Weight	6.5 kg
Warranty	5 Years
Certification	CE, ROHS

Emergency (Optional)

BLF	Lumen Output
12%	444 lm
11%	451 lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0–60 °C
Power Efficiency	95%
Certification	CE, ROHS

