

Terum Plus 600x1200



Performance

| Lumen Output | Wattage | lm/cW |
|----------------|---------|-------|
| 3702lm (4000K) | 27.4 W | 135.1 |
| 4104lm (4000K) | 30.6 W | 134.1 |

| | |
|----------------------------------|--------------------|
| Diffuser | Microprism |
| Rated Supply Voltage | 220–240 V |
| AC Voltage Range | 198–264 V |
| Mains Frequency | 50/60 Hz |
| Output LF Current Ripple @ 120Hz | <1% |
| Overvoltage Protection | 320 V |
| In-rush Current | 12 A |
| THD | <5% |
| Dimming Type (Optional) | DALI |
| Operating Temperature | -25 +60 °C |
| UGR Rating | <19 |
| Colour Rendering (3 SDCM) | Ra>82 |
| Longevity (L70/B10) | 60,000 hours |
| IP Rating | IP44 |
| Dimensions | 1195 x 295 x 10 mm |
| Weight | 3.8 kg |
| Warranty | 5 Years |
| Certification | CE, ROHS |

Emergency (Optional)

| BLF | Lumen Output |
|-----|--------------|
| 12% | 444lm |
| 11% | 451lm |

| | |
|-----------------------|----------------------------------|
| Emergency Duration | 3 Hours |
| Recharge Period | 24 Hours |
| Battery Type | LiFePO4 (Lithium Iron Phosphate) |
| Battery Pack | 3 x 3.2V 1.5Ah |
| Parasitic Load | 1.2W |
| Operating Temperature | 0–60 °C |
| Power Efficiency | 95% |
| Certification | CE, ROHS |

