

# Rida Track



The Rida is a compact adjustable track mounted spotlight which is compatible with Powergear, Global and other track systems.

The luminaire can be supplied in with single and three phase versions and can also be used with DALI dimming tracks.

This luminaire is construction from two die-cast parts – the heastsink and bezel. These components are held together at the point of articulation for ease of maintenance.

## Product

Rida	APL-T
------	-------

## Lumen Output

1494lm	/1494
1868lm	/1868
2491lm	/2491

## Colour Temperature

3000K	/3K
4000K	/4K
6500K	/6K

## Beam Angle

36° Beam	/36
45° Beam	/45

## Standard Colours\*

White	RAL9016
White	RAL9010
Black	RAL9005
*Other colours available upon special request	

## Mounting

Track Mounted – Global, Powergear, Stucchi, Unipro
--

## Dimming

Fixed output as default	
DALI dimming	-DA
Switch dim/Touch dim	-SD
Mains dimming	-MD
Casambi	-CA

Lumen Output	Wattage	l/cW
1868lm (4000K)	15.1W	123.7
2491lm (4000K)	20.1W	123.9

## Technical Data

<b>IP Rating</b>	<b>IP20</b>
<b>Construction</b>	<b>Diecast Aluminium</b>
<b>RAL colour (standard)</b>	<b>9016 9010 9005</b>
<b>Mounting Method</b>	<b>Track mounted: Global Powergear Stucchi Unipro</b>
<b>Protective class</b>	<b>1</b>
<b>Impact Resistance (IK)</b>	<b>IK04</b>
<b>Warranty</b>	<b>5 Years</b>
<b>Certification</b>	<b>UKCA, CE, ROHS</b>

Rated Supply Voltage	220—240 V
AC Voltage Range	198—264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<3%
Overvoltage Protection	320 V
In-rush Current	2.5 A
THD	<10%
Power Factor	95%
Parasitic Load	0.8W
Operating Temperature	-25 +60 °C

Dimensions (adapter)	260x32mm
Dimensions (spotlight)	Ø104 x 80mm
Weight	1.7 kg

