Dome



The Dome is a **Ø**180mmm large area downlight perfect for use in working areas due to its low glare performance uniform out-

The heatsink is made from die-cast aluminium which houses the LED module. The bezel of the downlight is machined from aluminium ensuring a constant high quality finish with no surface blemishes. The product is then retained in the ceiling by two swing arms to allow for a secure installation.

Product

Dome	DOM/

Lumen Output

1489lm	/1489
1985lm	/1985

Colour Temperature

3000K	/3K
4000K	/4K
6500K	/6K

Standard Colours*

White	RAL9016
White	RAL9010
Black	RAL9005
*Other colours available upon special request	

Mounting

|--|

Dimming

Fixed output as default	
DALI dimming	-DA
Switch dim/Touch dim	-SD
Mains dimming	-MD
Casambi	-CA

Emergency

No emergency facility as default	
3 hour internal pack	-E1
3 hour internal pack with self-test function	-E2
3 hour integral pack with DALI reporting function	-E3









Lighting Data

Lumen Output	Wattage	ll/cW
1489lm	15.4W	96.7
1985lm	20.5W	96.8

сст	3000K 4000K 6500K
Light Source	СОВ
SDCM	3
Longevity (L70/B10)	60,000 Hours
Colour Rendering	RA>82
UGR	<19

Technical Data

IP Rating	IP44
Construction	Diecast Aluminium
RAL colour (standard)	9016 9010 9005
Mounting Method	Recessed
Protective class	SELV
Impact Resistance (IK)	IK07
Warranty	5 Years
Certification	UKCA, CE, ROHS

Electrical Data


Rated Supply Voltage	220-240 V
AC Voltage Range	198-264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<5%
Overvoltage Protection	320 V
In-rush Current	14 A
THD	<10%
Power Factor	0.95
Parasitic Load	1.0 W
Operating Temperature	-25 +60 °C

Emergency Data

BLF	Lumen Output
18%	270lm
14%	270lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0-60 °C
Power Efficiency	95%
Certification	UKCA, CE, ROHS

Standard Photometry



Dimensions

Fixing Centres	Ø160mm
Dimensions	Ø180 x 60 mm
Weight	1.9kg



