

Brevis D Mini



The Brevis D Mini (Diffuser) is a Ø130mm small downlight which can be surface (standard) or suspended mounted.

The heatsink is built into the body of the product which enables the downlight to run at cool temperatures without the common need for vents in the vertical walls. The Brevis D Mini therefore has a minimalist architectural appearance without any visible fixings and very light weight thanks to its aluminium construction.

Product

Brevis D Mini	BRE/D/M
---------------	---------

Lumen Output

1154lm	/1154
1731lm	/1731

Colour Temperature

3000K	/3K
4000K	/4K
6500K	/6K

Beam Angle

90° Beam	/90
----------	-----

Standard Colours*

White	RAL9016
White	RAL9010
Black	RAL9005
*Other colours available upon special request	

Mounting

Surface mounted as default	
Suspended - 2.0m suspension kit complete with ceiling rose	-S

Dimming

Fixed output as default	
DALI dimming	-DA
Switch dim/Touch dim	-SD
Mains dimming	-MD
Casambi	-CA

Lighting Data

Lumen Output	Wattage	lm/cW
1154lm	10.1W	114.3
1731lm	15.2W	113.9

CCT	3000K 4000K
Light Source	SMD
SDCM	3
Longevity (L70/B10)	60,000 Hours
Colour Rendering	RA>82
UGR	<22


Technical Data

IP Rating	IP44 (Surface
Construction	Diecast Aluminium
RAL colour (standard)	9016 9010
Mounting Method	Surface
Protective class	Class 1
Impact Resistance (IK)	IK04
Warranty	5 Years
Certification	UKCA, CE, ROHS

Electrical Data

Rated Supply Voltage	220–240 V
AC Voltage Range	198–264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<5%
Overvoltage Protection	320 V
In-rush Current	2.5 A
THD	<10%
Power Factor	0.95
Parasitic Load	0.8 W
Operating Temperature	-25 +60 °C

Standard Photometry



Dimensions

Fixing Centres	Ø110mm
Dimensions	Ø130 x 100mm
Weight	2.2 kg

