



Performance

Lumen Output	Wattage	lm/cW
1202lm (4000K)	11.5 W	104.5
1601lm (4000K)	15.6 W	102.4
2005lm (4000K)	19.7 W	101.9
2402lm (4000K)	23.2 W	103.5
2805lm (4000K)	27.7 W	101.3

Rated Supply Voltage	220–240 V
AC Voltage Range	198–264 V
Mains Frequency	50/60 Hz
Output LF Current Ripple @ 120Hz	<5%
Overvoltage Protection	320 V
In-rush Current	1.5 A
THD	<10%
Dimming Type	DALI
Operating Temperature	-25 +60 °C
Colour Rendering	Ra>82
Longevity (L70/B10)	60,000 hours
IP Rating	IP54
Cutout	Ø160mm
Dimensions	Ø180 x 60mm
Weight	1.2 kg
Warranty	5 Years
Certification	CE, ROHS

Emergency (Optional)

EOF	Lumen Output
38%	457 lm
28%	448 lm
22%	441 lm
19%	456 lm
16%	449 lm

Emergency Duration	3 Hours
Recharge Period	24 Hours
Battery Type	LiFePO4 (Lithium Iron Phosphate)
Battery Pack	3 x 3.2V 1.5Ah
Parasitic Load	1.2W
Operating Temperature	0–60 °C
Power Efficiency	95%
Certification	CE, ROHS

