

Brevis R



The Brevis R (Recessed light source) is a $\varnothing 200\text{mm}$ large area downlight which can be surface (Standard) or suspended mounted.

The heatsink is built into the body of the product which enables the downlight to run at cool temperatures without the common need for vents in the vertical walls. The Brevis R therefore has a minimalist architectural appearance without any visible fixings and very light weight thanks to its aluminium construction.

The downlight also has an IP44 rating when surface mounted.

Product

Brevis R	BRE/R
----------	-------

Lumen Output

1872lm	/1872
2496lm	/2496

Colour Temperature

3000K	/3K
4000K	/4K
6500K	/6K

Beam Angle

60° Beam	/60
----------	-----

Standard Colours*

White	RAL9016
White	RAL9010
Black	RAL9005
*Other colours available upon special request	

Dimming

Fixed output as default	
DALI dimming	-DA
Switch dim/Touch dim	-SD
Mains dimming	-MD
Casambi	-CA

Mounting

Surface mounted as default	
Suspended - Flex only	-S
Suspended - $\varnothing 120\text{mm}$ rose (Standard)	-S1

Emergency

No emergency facility as default	
3 hour internal pack	-E1
3 hour internal pack with self-test function	-E2
3 hour integral pack with DALI reporting function	-E3

